



SVT 28



SVT 40



SVL 50



SVL 80

NEW

新品



VS 200/180



SVL 20/250

NEW

新品



SVL 450

型号	编号	流量		最大压力		额定温度	进水口	出水口	维修包编号	KG	KG
		l/min	gpm	bar	psi					重量	件/箱
安全阀											
SVT 28	0215010200	25	6,6	280	4060	90°C	2x3/8"GF	3/8"GF	4079900012	390	24
SVT 40	0215010420	25	6,6	400	5800	90°C	2x3/8"GF	3/8"GF	4079900034	490	5
SVL 50	4073500003	100	26,4	560	8100	90°C	1/2"GF	1/2"GF	4079900048	1420	1
SVL 80	4073201008	60	16	900	13050	90°C	3/8"GF	1/2"GF	4079900072	2000	1
	4073201009	60	16	900	13050	90°C	Rc 3/8 F	1/2"GF	4079900072	2000	1
VS 200/180	60.5100.15	200	53	200	2900	90°C	3/4"GF	1/2"GF	60.5110.24	820	4
SVL 20/250	4073500006	250	66	200	2900	90°C	3/4"GF	3/4"GF	4079900052	1140	1
SVL 450	4073500001	450	120	220	3200	90°C	1" GF	1" GF	4079900036	4650	1
	4073500002	450	120	330	4800	90°C	1" GF	1" GF	4079900036	4800	1

- 安全阀需安装人员正确调试后才能起到安全保护功能