




NEW
新品



技术特点：

这款喷头采用反冲式结构和自旋转式喷嘴，可以有效的清洗污水管和墙面。旋转喷嘴可配置4款可更换的顶头，用途特点分别是：喷洒、钻孔、碳合金、切割。

应用范围：

- 管道内泥沙的疏通和清洗，淤泥清洗，碎石清理（钻孔头），矿床清理，砂石清洗（碳合金头）
- 有效去除杂草树枝（切割头）

型号	编号	 流量	 最大压力	额定 温度	接口规格	后喷嘴 数量	前喷嘴 数量	喷嘴 尺寸	孔径	清洗管道 内壁直径	 重量	 件/箱	维修包编号	 件/箱	
		bar	psi						Ø mm	mm	g	件/箱		件/箱	
喷嘴															
SNCH 旋转反冲喷嘴	4052800000	见图表	300	4350	160°C	1/2" GF	3-M 6x6	6-M 6x6	20	35 x 77	50÷150 *	400	1	4059900046	1
	4052800001		300	4350	160°C	1/2" GF	3-M 6x6	6-M 6x6	30	35 x 77	50÷150 *	400	1	4059900047	1
	4052800002		300	4350	160°C	3/4" GF	6-M 6x6	4-M 6x6	30	50 x 100	100÷200 *	800	1	4059900048	1
	4052800003		300	4350	160°C	3/4" GF	6-M 6x6	4-M 6x6	40	50 x 100	100÷200 *	800	1	4059900049	1
	4052800004		300	4350	160°C	1" GF	6-M 6x6	4-M 6x6	50	50 x 100	100÷200 *	800	1	4059900050	1
	4052800005		300	4350	160°C	1" GF	6-M 6x6	4-M 6x6	70	50 x 100	100÷200 *	800	1	4059900051	1

* 管径超过100mm (3.93英寸) 时需要导向架

材质：硬质不锈钢AISI A420抛光