



技术特点：

鹅卵石形喷头特别适合清洗污水管道的弯曲处和转角处。

应用范围：

- 住宅排污管道疏通
- 清洗管道转弯处
- 碎屑、碎石、皂液和污泥清洗
- 公共卫生间清洗

型号	编号	 流量	 最大压力	额定 温度	接口规格	后喷嘴 数量	前喷嘴 数量	喷嘴 尺寸	孔径	清洗管道 内壁直径	 重量	 件/箱	维修包编号	 件/箱		
				bar	psi					Ø mm	mm	g				
喷嘴																
SNO反冲喷嘴	4052600015	见图表	见图表	300	4350	160°C	1/2" GF	6-M 6x8	1-M 6x8	20	42 x 58	50÷100	300	1	4059900032	1
	4052600016			300	4350	160°C	1/2" GF	6-M 6x8	1-M 6x8	30	42 x 58	50÷100	300	1	4059900033	1
	4052600017			300	4350	160°C	3/4" GF	6-M 6x8	1-M 6x8	30	48 x 60	60÷150	360	1	4059900033	1
	4052600024			300	4350	160°C	3/4" GF	6-M 6x8	1-M 6x8	40	48 x 60	60÷150	360	1	4059900034	1
	4052600025			300	4350	160°C	3/4" GF	6-M 6x8	1-M 6x8	50	48 x 60	60÷150	360	1	4059900035	1
	4052600026			300	4350	160°C	3/4" GF	6-M 6x8	1-M 6x8	60	48 x 60	60÷150	360	1	4059900036	1
	4052600027			300	4350	160°C	1" GF	6-M 6x8	1-M 6x8	50	60 x 78	100÷300	800	1	4059900035	1
	4052600028			300	4350	160°C	1" GF	6-M 6x8	1-M 6x8	60	60 x 78	100÷300	800	1	4059900036	1
	4052600029			300	4350	160°C	1" GF	6-M 6x8	1-M 6x8	80	60 x 78	100÷300	800	1	4059900037	1
喷嘴罩维修包编号												U00001030	1			

材质：镀镍钢