



技术特点：
三棱喷头，3个侧面喷嘴和1个正面喷嘴。这款喷头在面对沉淀物清洗工作时拥有优秀的穿透力和强劲的喷射力。陶瓷喷嘴可适用污水和水循环环境。

应用范围：

- 管道沉淀物疏通和清洗
- 破石、破冰、碎石、碎混凝土、树枝

型号	编号			额定温度	接口规格	后喷嘴数量	前喷嘴数量	喷嘴尺寸	孔径	清洗管道内壁直径			维修包编号		
		流量	最大压力												
		bar	psi					Ø mm		mm	g	件/箱		件/箱	
喷嘴															
SNT反冲喷嘴	4052600009	见图表	300	4350	160℃	1/2" GF	3-M 6x6	4-M 6x6	20	30 x 55	40÷100	140	1	4059900038	1
	4052600010		300	4350	160℃	1/2" GF	3-M 6x6	4-M 6x6	30	30 x 55	40÷100	140	1	4059900039	1
	4052600011		300	4350	160℃	3/4" GF	6-M 6x8	4-M 6x8	30	48 x 80	60÷200	500	1	4059900040	1
	4052600030		300	4350	160℃	3/4" GF	6-M 6x8	4-M 6x8	40	48 x 80	60÷200	500	1	4059900041	1
	4052600031		300	4350	160℃	3/4" GF	6-M 6x8	4-M 6x8	50	48 x 80	60÷200	500	1	4059900042	1
	4052600032		300	4350	160℃	3/4" GF	6-M 6x8	4-M 6x8	60	48 x 80	60÷200	500	1	4059900043	1
	4052600033		300	4350	160℃	1" GF	6-M 8x10	4-M 8x10	50	58 x 110	70÷300	1000	1	4059900042	1
	4052600034		300	4350	160℃	1" GF	6-M 8x10	4-M 8x10	60	58 x 110	70÷300	1000	1	4059900044	1
	4052600035		300	4350	160℃	1" GF	6-M 8x10	4-M 8x10	80	58 x 110	70÷300	1000	1	4059900045	1

材质：镀镍钢