

喷嘴



喷嘴 - MGA



陶瓷材质

MGA系列 - 空心圆锥形喷嘴

特点

- 陶瓷材质，含99%氧化铝
- 推荐压力范围 2.7 - 20.7 bar
- 40°喷雾角度
- 更小的雾化颗粒，喷洒均匀度高
- 叶面覆盖及渗透率高
- 适用于系统性喷洒杀菌剂和杀虫剂

NOZZLE SPACING 0,50 m - SPRAYING VOLUME (l/ha)

编号	类型	bar	psi	VMD	1/min	4	5	6	7	8	9	10	12	14	16	18	20	25
8259590	MGA 40-01	2,7	40	MF	0,35	135	108	90	77	68	60	54	45	39	34	30	27	22
		4,8	70	MF	0,50	150	120	100	86	75	67	60	50	43	38	33	30	24
		6,9	100	MF	0,59	172	140	116	101	89	79	71	59	51	44	39	35	28
		10,4	150	MF	0,68	204	163	136	117	102	91	82	68	58	51	45	41	33
		13,8	200	MF	0,82	246	197	164	141	123	109	98	82	70	62	55	49	39
8259591	MGA 40-015	2,7	40	MF	0,57	171	137	114	98	86	76	68	57	49	43	38	34	27
		4,8	70	MF	0,67	201	161	134	115	101	89	80	67	57	50	45	40	32
		6,9	100	MF	0,78	230	186	154	135	120	108	90	77	68	60	54	49	43
		10,4	150	MF	1,05	315	252	210	180	158	140	126	105	90	79	70	63	50
		13,8	200	MF	1,25	375	300	252	210	180	158	140	126	105	90	79	70	63
8259592	MGA 40-02	2,7	40	F	0,53	459	367	306	262	230	204	184	153	131	115	102	92	73
		4,8	70	F	0,75	225	180	150	129	113	100	90	75	64	56	50	45	36
		6,9	100	MF	1,00	300	240	200	171	150	133	120	100	86	75	67	60	48
		10,4	150	MF	1,20	360	288	240	206	180	160	144	120	103	90	80	72	58
		13,8	200	MF	1,65	495	396	330	283	248	220	198	165	141	124	110	99	79
8259593	MGA 40-025	2,7	40	MF	0,88	264	213	176	151	132	117	104	86	75	68	59	53	42
		4,8	70	MF	1,20	375	300	250	214	188	167	150	125	107	94	83	75	60
		6,9	100	MF	1,50	450	360	300	257	225	200	180	150	129	113	100	90	72
		10,4	150	MF	1,81	543	434	362	310	272	241	217	181	155	136	121	109	87
		13,8	200	MF	2,07	621	497	414	355	311	276	248	207	177	155	138	124	99
8259594	MGA 40-03	2,7	40	F	0,95	285	228	190	163	143	127	114	95	81	71	63	57	46
		4,8	70	F	1,15	345	276	230	197	173	153	138	115	99	86	77	69	55
		6,9	100	MF	1,33	399	319	266	228	200	177	160	133	114	100	89	80	64
		10,4	150	MF	1,60	540	432	360	309	270	240	216	180	154	135	120	108	86
		13,8	200	MF	2,20	660	528	440	377	330	293	264	220	189	165	147	132	106
8259595	MGA 40-035	2,7	40	MF	1,02	345	300	252	214	188	167	150	125	107	94	83	75	60
		4,8	70	MF	1,20	375	300	250	214	188	167	150	125	107	94	83	75	60
		6,9	100	MF	1,50	450	360	300	257	225	200	180	150	129	113	100	90	72
		10,4	150	MF	1,81	543	434	362	310	272	241	217	181	155	136	121	109	87
		13,8	200	MF	2,07	621	497	414	355	311	276	248	207	177	155	138	124	99
8259596	MGA 40-04	2,7	40	F	1,08	360	312	264	226	200	177	160	133	114	100	89	80	64
		4,8	70	F	1,28	564	451	376	322	282	251	226	188	161	141	125	113	94
		6,9	100	MF	1,50	450	360	300	257	225	200	180	150	129	113	100	90	72
		10,4	150	MF	1,81	543	434	362	310	272	241	217	181	155	136	121	109	87
		13,8	200	MF	2,07	621	497	414	355	311	276	248	207	177	155	138	124	99
8259597	MGA 40-05	2,7	40	F	1,28	564	451	376	322	282	251	226	188	161	141	125	113	94
		4,8	70	F	1,28	564	451	376	322	282	251	226	188	161	141	125	113	94
		6,9	100	MF	1,50	450	360	300	257	225	200	180	150	129	113	100	90	72
		10,4	150	MF	1,81	543	434	362	310	272	241	217	181	155	136	121	109	87
		13,8	200	MF	2,07	621	497	414	355	311	276	248	207	177	155	138	124	99



陶瓷材质

MGA系列 - 空心圆锥形喷嘴

特点

- 陶瓷材质，含99%氧化铝
- 推荐压力范围 2.7 - 20.7 bar
- 60°喷雾角度
- 更小的雾化颗粒，喷洒均匀度高
- 叶面覆盖及渗透率高
- 适用于系统性喷洒杀菌剂和杀虫剂

NOZZLE SPACING 0,50 m - SPRAYING VOLUME (l/ha)

8259583	MGA 60-02	6.9	100	MF	1.20	360	288	240	206	180	160	144	120	103	90	80	72	58
		10.4	150	MF	1.42	426	341	284	243	213	189	170	142	127	107	95	85	68
		13.8	200	MF	1.65	495	396	330	283	248	220	198	165	141	124	110	99	79
		2.7	40	MF	0.305	609	487	406	348	305	271	244	203	174	152	135	122	97
		4.8	70	F	0.95	285	228	190	163	143	127	114	95	81	71	63	57	46
8259584	MGA 60-025	3.8	55	MF	1.10	330	264	220	189	165	147	132	110	94	83	73	66	53
		4.8	70	MF	1.25	375	300	250	214	188	167	150	125	107	94	83	75	60
		6.9	100	MF	1.50	450	360	300	257	225	200	180	150	129	113	100	90	72
		10.4	150	MF	1.81	543	434	362	310	272	241	217	181	155	136	121	109	87
		13.8	200	MF	2.07	621	497	414	355	311	276	248	207	177	155	138	124	99
8259585	MGA 60-03	2.7	40	MF	0.51	253	202	167	143	127	114	95	81	71	63	57	46	
		2.7	40	F	1.15	345	276	230	197	173	153	138	115	99	86	77	69	
		3.8	55	F	1.33	399	319	266	228	200	177	160	133	114	100	89	80	
		4.8	70	MF	1.50	450	360	300	257	225	200	180	150	129	113	100	90	
		6.9	100	MF	1.80	540	432	360	309	270	240	216	180	154	135	120	108	
8259586	MGA 60-035	10.4	150	MF	2.20	660	528	440	377	330	293	264	220	189	165	147	132	106
		13.8	200	MF	2.50	750	600	500	429	375	333	300	250	214	188	167	150	124
		2.7	40	MF	3.00	900	720	600	514	450	400	360	307	257	225	200	180	144
		2.7	40	F	0.95	285	228	190	163	143	127	114	95	81	71	63	57	
		3.8	55	F	1.10	330	264	220	189	165	147	132	110	94	83	73	66	
8259587	MGA 60-035	4.8	70	MF	1.25	375	300	250	214	188	167	150	125	107	94	83	75	60
		6.9	100	MF	1.50	450	360	300	257	225	200	180	150	129	113	100	90	
		10.4	150	MF	1.81	543	434	362	310	272	241	217	181	155	136	121	109	
		13.8	200	MF	2.07	621	497	414	355	311	276	248	207	177	155	138	124	
		2.7	40	F	1.61	483	386	322	276	242	215	193	171	151	131	117	102	
8259588	MGA 60-04	3.8	55	F	1.18	364	451	362	322	282	251	226	188	161	141	125	113	
		4.8	70	F	2.10	630	504	420	376	335	315	280	252	210	180	158	140	
		6.9	100	MF	2.55	612	510	437	383	340	306	265	219	191	171	153	132	
		10.4	150	MF	3.10	930	744	620	531	463	413	372	310	266	237	207	186	
		13.8	200	MF	3.50	1050	840	700	600	525	467	420	350	300	263	233	210	
8259589	MGA 60-05	2.7	40	MF	4.30	1290	1032	860	737	645	576	516	430	367	322	282	246	
		2.7	40	F	1.96	588	470	392	336	294	261	235	196	168	147	131	118	
		3.8	55	F	2.38	714	571	476	408	357	317	268	238	204	179	159	143	
		4.8	70	F	2.65	765	612	510	437	383	340	306	265	219	191	171	153	
		6.9	100	MF	3.00	900	720	600	514	450	400	360	307	257	225	200		
8259590	MGA 60-06	10.4	150	MF	3.70	1110	888	740	634	555	493	444	370	317	278	242	222	
		13.8	200	MF	4.30	1290	1032	860	737	645	576	516	430	367	322	282	246	
		2.7	40	MF	5.20	1560	1248	1040	891	781	693	624	520	446	390	347	312	
		2.7	40	F	2.34	702	562	468	401	351	313	281	234	201	176	156	140	
		3.8	55	F	2.78	1294	1032	860	737	645	576	516	430	367	322	282	246	
8259591	MGA 60-06	4.8	70	F	2.95	885	708	590	506	443	393	343	295	253	221	197	174	
		6.9	100	F	3.65	1093	876	730	626	548	487	438	365	313	274	243	219	
		10.4	150	MF	4.27	1236	1016	846	728	635	589	540	452	375	319	285	260	
		13.8	200	MF	5.14	1465	1236	1030	883	773	687	618	481	386	343	307	275	
		2.7	40	MF	6.25	1875	1500	1250	1071	938	833	742	635	549	471	405	365	

20.7 bar

MGA 系列 - 空心圆锥喷嘴

特点

陶瓷材质，含 90% 氧化铝

推荐压力范围 4.8-20.7 bar

80° 喷雾角度

更小的雾化颗粒，喷射均匀度高

叶面覆盖及渗透率高