



低压控制元件

MOD 型号	流量		压力		分段数	KG 重量	尺寸规格			进水口	回水口	出水口
	l/min	gpm	bar	psi			LxHxW mm			mm	mm	mm
ECM	160	42,3	20	290	2 - 4 - 6	1,2 ÷ 1,6	153÷306	250	252	Ø25	Ø25	Ø12 (10-20 Opt)
UCM	160	42,3	20	290	2 - 4 - 6	2,3 ÷ 2,7	235÷376	320	334	Ø25	Ø25	Ø12 (10-20 Opt)
GS 20 S	80	21,1	20	290	3	1,6	240	220	205	Ø20	Ø18	Ø10
GS 25 S	50	13,2	20	290	2	1	229	279	167	Ø25	Ø18	Ø10
GS 35 S	100	26,4	20	290	4	1,7	314	212	257	Ø25	Ø25	Ø10
RM 20 S	80	21,1	20	290	3	1,6	257	193	266	Ø25	Ø25	Ø10
VDR 20 S	130	34,3	20	290	4	2,2	237	308	300	Ø25	Ø25	Ø10
VSP 200	200	53	20	290	TBA	0,5	110	220	72	Ø1"¼	Ø1	Ø1"¼
VSP 400	400	105	20	290	TBA	1,1	88	264	137,5	Ø1"½	Ø1"½	Ø2"
VSP 600	600	158	20	290	TBA	3,1	110	377	187	Ø2"	Ø2"	Ø2"



ECM
AR 70bp÷AR160bp



UCM
AR 70bp÷AR160bp



GS 25 S
AR 45bp



GS 35 S
AR45bp, AR 80bp



VSP 200 / VSP 400 / VSP 600



GS 20 S
AR 70bp



RM 20 S
AR 70bp÷AR115bp



VDR 20 S
AR 70bp÷AR135bp

控制元件

